

2014 SILVERADO 1500 REGULAR CAB SPECIFICATIONS

Overview

Models:	C/K 15703: regular cab 6' 6" box, 2WD and 4WD C/K 15903: regular cab 8' box, 2WD and 4WD
Body style / driveline:	2/3-passenger regular cab, half-ton, 2- and, 4-wheel drive light-duty pickups available with 6' 6" box and 8' box
EPA vehicle class:	full-size truck
Manufacturing location:	Fort Wayne, Ind.
Key competitors:	Ford F-150, Ram 1500, Toyota Tundra

Engines

	EcoTec3 4.3L V-6 FlexFuel (LV3)	EcoTec3 5.3L V-8 FlexFuel (L83)
Type:	4.3L V-6	5.3L V-8
Displacement (cu in / cc):	262 / 4300	325 / 5328
Bore & stroke (in / mm):	3.92 x 3.62 / 99.6 x 92	3.78 x 3.62 / 96 x 92
Block material:	cast aluminum	cast aluminum
Cylinder head material:	cast aluminum	cast aluminum
Valvetrain:	overhead valve, two valves per cylinder, variable valve timing	overhead valve, two valves per cylinder, variable valve timing
Ignition system:	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires
Fuel delivery:	direct fuel injection with Active Fuel Management	direct fuel injection with Active Fuel Management
Compression ratio:	11.0:1	11.0:1
Horsepower (hp / kW @ rpm):	285 / 212 @ 5300 (gas – SAE certified) 297 / 221 @ 5300 (E85 – SAE certified)	355 / 250 @ 5600 (gas – SAE certified) 380 / 283 @ 5600 (E85 – SAE certified)
Torque (lb-ft / Nm @ rpm):	305 / 413 @ 3900 (gas – SAE certified) 330 / 447 @ 3900 (E85 – SAE certified)	383 / 519 @ 4100 (gas – SAE certified) 416 / 564 @ 4100 (E85 – SAE certified)
Recommended fuel:	regular unleaded or E85	regular unleaded or E85
Maximum engine speed (rpm):	5800	5800
Emissions controls:	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor
Estimated fuel economy (city / hwy):	TBD	16 / 23 (2WD) 16 / 22 (4WD)

Transmission

	Hydra-Matic 6L80
Type:	six-speed automatic
Gear ratios (:1):	
First:	4.03
Second:	2.36
Third:	1.53
Fourth:	1.15
Fifth:	0.85
Sixth:	0.67
Reverse:	3.06
Final drive ratio (std. & avail.):	3.08, 3.23 or 3.42; 3.73 with Max Trailering Package

Chassis / Suspension

Front:	independent coil-over-shock; twin-tube shock absorbers
Rear:	solid axle with semi-elliptic, variable-rate, two-stage multileaf springs; splayed

	shock absorbers; twin-tube shocks
Steering type:	electric power-assisted rack-and-pinion
Steering ratio:	18.4:1
Steering wheel turns, lock-to-lock:	3.46
Turning circle, curb-to-curb (ft / m):	2WD with 6' 6" box: 40 / 12.2 4WD with 6' 6" box: 40 / 12.2 2WD with 8' box: 44 / 13.4 4WD with 8' box: 44 / 13.4

Brakes

Type:	power-assisted, four-wheel disc, four-wheel ABS, with Duralife™ rotors; vented front rotors
Rotor diameter x thickness (in / mm)	front: 13 x 1.18 / x 330 x 30 rear: 13.6 x 0.79 / 345 x 20
Total swept area (sq in / sq cm)	front: 250 / 1612 rear: 252 / 1628

Wheels / Tires

Wheel size & type:	17 x 8-in. steel (std. 1WT) 17 x 8-in. stainless steel-clad (std. 2WT) 17 x 8-in. bright machined aluminum (std. LT) 18 x 8.5-in. bright machined aluminum (avail. LT) 20 x 9-in. polished aluminum (avail. LT)
Tires:	P245/70R17 all-season, blackwall P265/70R17 all-season, blackwall P265/70R17 all-terrain, blackwall LT265/70R17 all-terrain, blackwall P265/65R18 all-season, blackwall P265/65R18 all-terrain, blackwall or white-outlined letters P275/55R20 all-season blackwall P275/55R20 all-terrain blackwall

Dimensions

Exterior

	Regular Cab with 6' 6" box	Regular Cab with 8' box
Wheelbase (in / mm):	119 / 3023	133 / 3378
Overall length (in / mm):	205.6 / 5221	224.4 / 5701
Overall width (in / mm):	80 / 2032	80 / 2032
Overall height (in / mm)		
2WD:	74.0 / 1879	73.5 / 1867
4WD:	74.1 / 1883	73.8 / 1875
Track (in / mm)		
2WD front:	68.8 / 1747	68.8 / 1747
2WD rear:	67.6 / 1716	67.6 / 1716
4WD front:	68.7 / 1745	68.7 / 1745
4WD rear:	67.6 / 1716	67.6 / 1716
Min. running ground clearance (in / mm):		
2WD:	8.2 / 209	8.3 / 212
4WD:	8.6 / 218	8.8 / 223
Ground to top of load floor (in / mm):		
2WD:	36.3 / 922	35.9 / 913
4WD:	36.2 / 919	35.6 / 905
Step-in height		
2WD:	22.6 / 573	22.4 / 568
4WD:	22.8 / 578	22.5 / 572
Approach angle (deg)		

2WD:	14.5	14.7
4WD:	15.2	15.5
Breakover angle (deg)		
2WD:	24.4	21.1
4WD:	24.1	21.3
Departure angle (deg)		
2WD:	25.0	23.7
4WD:	24.9	23.4

Cargo box

	Regular Cab with 6' 6" box	Regular Cab with 8' box
Cargo volume (cu ft / L):	61 / 1728	76.3 / 2162
Length at floor (in / mm):	78.9 / 2003	97.8 / 2483
Width at floor (in / mm):	64.6 / 1642	64.6 / 1642
Width between wheelhousings (in / mm):	51 / 1296	51 / 1296
Tailgate width (in / mm):	62.2 / 1579	62.2 / 1579
Inside height (in / mm):	21.1 / 536	21.1 / 536

Interior

	Regular Cab
Headroom (in / mm):	42.4 / 1077
Legroom (in / mm):	45.3 / 1150
Shoulder room (in / mm):	66 / 1677
Hip room (in / mm):	60.7 / 1543

Curb weight & payload

	GVWR (lb / kg)	Minimum Curb Weight (lb / kg)	Max. Payload (lb / kg)	Weight Distribution (% front / rear)
2WD:				
Regular Cab, 6' 6" box	6500 / 2948 (4.3L) 6600 / 2994 (5.3L)	4387 / 1990 (4.3L) 4503 / 2042 (5.3L)	2088 / 947 (4.3L) 2072 / 940 (5.3L)	58 / 42
Regular Cab, 8' box	6700 / 3039 (4.3L) 6800 / 3084 (5.3L)	4567 / 2071 (4.3L) 4673 / 2119 (5.3L)	2108 / 956 (4.3L) 2102 / 953 (5.3L)	58 / 42
4WD:				
Regular Cab, 6' 6" box	6700 / 3039 (4.3L) 6800 / 3084 (5.3L)	4587 / 2080 (4.3L) 4707 / 2135 (5.3L)	2088 / 947 (4.3L) 2068 / 938 (5.3L)	60 / 40
Regular Cab, 8' box	6900 / 3130 (4.3L) 7000 / 3175 (5.3L)	4816 / 2184 (4.3L) 4922 / 2232 (5.3L)	2059 / 934 (4.3L) 2053 / 931 (5.3L)	59 / 41

Capacities

	Regular Cab, 6' 6" box	Regular Cab, 8' box
Seating:	3	3
Fuel tank (gal / L):	26 / 98	34 / 128
	EcoTec3 4.3L	EcoTec3 5.3L
Engine oil (qt / L):	6 / 5.6 (Dexos 5W30)	8 / 7.5 (Dexos 0W20)
Cooling system (qt / L):	14.8 / 14	15.6 / 14.8

Trailer - maximum with ball hitch

2WD:	
Regular Cab, 6' 6" box	6400 / 2903 – 4.3L (3.23 axle) 9300 / 4218 – 5.3L (3.42 axle)
Regular Cab, 8' box	6300 / 2857 – 4.3L (3.23 axle) 10200 / 4626 – 5.3L (3.42 axle)
4WD:	
Regular Cab, 6' 6" box	7200 / 3266 – 4.3L (3.42 axle) 9100 / 4217 – 5.3L (3.42 axle)
Regular Cab, 8' box	7000 / 3175 – 4.3L (3.42 axle)

	9900 / 4490 – 5.3L (3.42 axle)
--	--------------------------------

Note: Information shown is current at time of publication. Visit <http://media.gm.com> for updates.

2014 CHEVROLET SILVERADO 1500 DOUBLE CAB SPECIFICATIONS

Overview

Models:	C/K 15753: double cab, 2WD and 4WD
Body style / driveline:	5/6-passenger double cab, half-ton, 2-and 4-wheel drive light-duty pickup with 6' 6" box
EPA vehicle class:	full-size truck
Manufacturing location:	Fort Wayne, Ind.
Key competitors:	Ford F-150, Ram 1500, Toyota Tundra, Nissan Titan

Engines

	EcoTec3 4.3L V-6 FlexFuel (LV3)	EcoTec3 5.3L V-8 FlexFuel (L83)	EcoTec3 6.2L V-8 FlexFuel (L86)
Type:	4.3L V-6	5.3L V-8	6.2L V-8
Displacement (cu in / cc):	262 / 4300	325 / 5328	376 / 6162
Bore & stroke (in / mm):	3.92 x 3.62 / 99.6 x 92	3.78 x 3.62 / 96 x 92	4.06 x 3.62 / 103.25 x 92
Block material:	cast aluminum	cast aluminum	cast aluminum
Cylinder head material:	cast aluminum	cast aluminum	cast aluminum
Valvetrain:	overhead valve, two valves per cylinder, variable valve timing	overhead valve, two valves per cylinder, variable valve timing	overhead valve, two valves per cylinder, variable valve timing
Ignition system:	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires
Fuel delivery:	direct fuel injection with Active Fuel Management	direct fuel injection with Active Fuel Management	direct fuel injection with Active Fuel Management
Compression ratio:	11.0:1	11.0:1	11.5:1
Horsepower (hp / kW @ rpm):	285 / 212 @ 5300 (gas – SAE certified) 297 / 221 @ 5300 (E85 – SAE certified)	355 / 250 @ 5600 (gas – SAE certified) 380 / 283 @ 5600 (E85 – SAE certified)	TBD
Torque (lb-ft / Nm @ rpm):	305 / 413 @ 3900 (gas – SAE certified) 330 / 447 @ 3900 (E85 – SAE certified)	383 / 519 @ 4100 (gas – SAE certified) 416 / 564 @ 4100 (E85 – SAE certified)	TBD
Recommended fuel:	regular unleaded or E85	regular unleaded or E85	regular unleaded or E85
Maximum engine speed (rpm):	5800	5800	6000
Emissions controls:	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor
Estimated fuel economy (city / hwy):	TBD	16 / 23 (2WD) 16 / 22 (4WD)	TBD

Transmission

	Hydra-Matic 6L80
Type:	six-speed automatic
Gear ratios (:1):	
First:	4.03
Second:	2.36
Third:	1.53

Fourth:	1.15
Fifth:	0.85
Sixth:	0.67
Reverse:	3.06
Final drive ratio (std. & avail.):	3.08, 3.23 or 3.42; 3.73 with Max Trailering Package

Chassis / Suspension

Front:	independent coil-over-shock; twin-tube shock absorbers; monotube shocks with Z71
Rear:	solid axle with semi-elliptic, variable-rate, two-stage multileaf springs; splayed shock absorbers; twin-tube shock absorbers; monotube shocks with Z71
Steering type:	electric power-assisted rack-and-pinion
Steering ratio:	16.3:1
Steering wheel turns, lock-to-lock:	3.03
Turning circle, curb-to-curb (ft / m):	2WD with 6' 6" box: 46.9 / 14.3 4WD with 6' 6" box: 46.9 / 14.3

Brakes

Type:	power-assisted, four-wheel disc, four-wheel ABS, with Duralife™ rotors; vented front rotors
Rotor diameter x thickness (in / mm)	front: 13 x 1.18 / x 330 x 30 rear: 13.6 x 0.79 / 345 x 20
Total swept area (sq in / sq cm)	front: 250 / 1612 rear: 252 / 1628

Wheels / Tires

Wheel size & type:	17 x 8-in. steel (std. 1WT) 17 x 8-in. stainless steel-clad (std. 2WT) 17 x 8-in. bright machined aluminum (std. LT, Z71 w/LT) 18 x 8.5-in. bright machined aluminum (std. LTZ, Z71 w/LTZ; avail. LT, Z71 w/LT) 20 x 9-in. polished aluminum (avail. LT, Z71 w/LT) 20 x 9-in. chrome aluminum (std. High Country; avail. LTZ, Z71 w/LTZ)
Tires:	P245/70R17 all-season, blackwall P265/70R17 all-season, blackwall P265/70R17 all-terrain, blackwall LT265/70R17 all-terrain, blackwall P265/65R18 all-season, blackwall P265/65R18 all-terrain, blackwall or white-outlined letter P275/55R20 all-terrain, blackwall P275/55R20 all-season, blackwall

Dimensions

Exterior

	Double Cab with 6' 6" box
Wheelbase (in / mm):	143.5 / 3645
Overall length (in / mm):	230 / 5843
Overall width (in / mm):	80 / 2032
Overall height (in / mm)	
2WD:	73.9 / 1876
4WD:	73.9 / 1877
Track (in / mm)	
2WD front:	68.9 / 1750
2WD rear:	67.9 / 1716
4WD front:	68.9 / 1750
4WD rear:	67.6 / 1716
Min. running ground	

clearance (in / mm):	
2WD:	8.5 / 216
4WD:	8.9 / 225
Ground to top of load floor (in / mm):	
2WD:	34.8 / 883
4WD:	34.5 / 876
Step-in height	
2WD:	22.3 / 566
4WD:	22.4 / 570
Approach angle (deg)	
2WD:	17.1
4WD:	17.9
Breakover angle (deg)	
2WD:	18.9
4WD:	19.1
Departure angle (deg)	
2WD:	23.4
4WD:	23.1

Cargo box

	Double Cab with 6' 6" box
Cargo volume (cu ft / L):	61 / 1728
Length at floor (in / mm):	78.9 / 2003
Width at floor (in / mm):	64.9 / 1642
Width between wheelhousings (in / mm):	51 / 1296
Tailgate width (in / mm):	62.2 / 1579
Inside height (in / mm):	21.1 / 536

Interior

	Double Cab, Front	Double Cab, Rear
Headroom (in / mm):	42.8 / 1087	38.7 / 982
Legroom (in / mm):	45.2 / 1150	34.6 / 880
Shoulder room (in / mm):	64.8 / 1647	65.8 / 1671
Hip room (in / mm):	60.7 / 1543	60.2 / 1530

Curb weight & payload

	GVWR (lb / kg)	Minimum Curb Weight (lb / kg)	Max. Payload (lb / kg)	Weight Distribution (% front / rear)
2WD:				
Double Cab, 6' 6" box	6900 / 3130 (4.3L) 7000 / 3175 (5.3L)	4860 / 2204 (4.3L) 4963 / 2251 (5.3L)	2015 / 914 (4.3L) 2012 / 912 (5.3L)	58 / 42
Double Cab, 6' 6" box – with Max Trailering Package	7200 / 3266 (5.3L)	5074 / 2301 (5.3L)	2101 / 953 (5.3L)	58 / 42
4WD:				
Double Cab, 6' 6" box	7100 / 3220 (4.3L) 7200 / 3266 (5.3L)	5104 / 2315 (4.3L) 5201 / 2359 (5.3L)	1971 / 894 (4.3L) 1974 / 895 (5.3L)	59 / 41
Double Cab, 6' 6" box – with Max Trailering Package	7200 / 3266 (5.3L)	5309 / 2408 (5.3L)	1866 / 846 (5.3L)	59 / 41

Capacities

	Double Cab, 6' 6" box
Seating:	5 or 6
Fuel tank (gal / L):	26 / 98

	EcoTec3 4.3L	EcoTec3 5.3L	EcoTec3 6.2L
Engine oil (qt / L):	6 / 5.6 (Dexos 5W30)	8 / 7.5 (Dexos 0W20)	8 / 7.5 (Dexos 0W20)
Cooling system (qt / L):	14.8 / 14	15.6 / 14.8	15.6 / 14.8

Trailer – maximum with ball hitch

2WD:	
Double Cab, 6' 6" box	6000 / 2721 – 4.3L (3.23 axle) 9900 / 4490 – 5.3L (3.42 axle)
Double Cab, 6' 6" box w/ Max Trailering Package	11500 / 5216 – 5.3L (3.73 axle)
4WD:	
Double Cab, 6' 6" box	6700 / 3039 – 4.3L (3.42 axle) 9600 / 4354 – 5.3L (3.42 axle)
Double Cab, 6' 6" box w/ Max Trailering Package	11200 / 5080 – 5.3L (3.73 axle)

Note: Information shown is current at time of publication. Visit <http://media.gm.com> for updates.

2014 CHEVROLET SILVERADO 1500 CREW CAB SPECIFICATIONS

Overview

Models:	C/K 15543: crew cab with 5' 8" box, 2WD and 4WD C/K 15743: crew cab with 6' 6" box, 2WD and 4WD
Body style / driveline:	5/6-passenger crew cab, half-ton, 2-and 4- wheel drive light-duty pickups, available with 5' 8" or 6' 6" box
EPA vehicle class:	full-size truck
Manufacturing location:	Silao, Mexico and Flint, Mich.
Key competitors:	Ford F150, Ram 1500, Toyota Tundra, Nissan Titan

Engines

	EcoTec3 4.3L V-6 FlexFuel (LV3)	EcoTec3 5.3L V-8 FlexFuel (L83)	EcoTec3 6.2L V-8 FlexFuel (L86)
Type:	4.3L V-6	5.3L V-8	6.2L V-8
Displacement (cu in / cc):	262 / 4300	325 / 5328	376 / 6162
Bore & stroke (in / mm):	3.92 x 3.62 / 99.6 x 92	3.78 x 3.62 / 96 x 92	4.06 x 3.62 / 103.25 x 92
Block material:	cast aluminum	cast aluminum	cast aluminum
Cylinder head material:	cast aluminum	cast aluminum	cast aluminum
Valvetrain:	overhead valve, two valves per cylinder, variable valve timing	overhead valve, two valves per cylinder, variable valve timing	overhead valve, two valves per cylinder, variable valve timing
Ignition system:	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires	coil near plug, platinum-tipped spark plugs, low-resistance spark plug wires
Fuel delivery:	direct fuel injection with Active Fuel Management	direct fuel injection with Active Fuel Management	direct fuel injection with Active Fuel Management
Compression ratio:	11.0:1	11.0:1	11.5:1
Horsepower (hp / kW @ rpm):	285 / 212 @ 5300 (gas – SAE certified) 297 / 221 @ 5300 (E85 – SAE certified)	355 / 250 @ 5600 (gas – SAE certified) 380 / 283 @ 5600 (E85 – SAE certified)	TBD
Torque (lb-ft / Nm @ rpm):	305 / 413 @ 3900 (gas – SAE certified) 330 / 447 @ 3900 (E85 – SAE certified)	383 / 519 @ 4100 (gas – SAE certified) 416 / 564 @ 4100 (E85 – SAE certified)	TBD
Recommended fuel:	regular unleaded or E85	regular unleaded or E85	regular unleaded or E85
Maximum engine speed	5800	5800	6000

(rpm):			
Emissions controls:	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor	close-coupled catalytic converter, Quick Sync 58X ignition, returnless fuel rail, fast-response O ² sensor
Estimated fuel economy (city / hwy):	TBD	16 / 23 (2WD) 16 / 22 (4WD)	TBD

Transmission

	Hydra-Matic 6L80
Type:	6-speed automatic
Gear ratios (:1):	
First:	4.03
Second:	2.36
Third:	1.53
Fourth:	1.15
Fifth:	0.85
Sixth:	0.67
Reverse:	3.06
Final drive ratio (std. & avail.):	3.08, 3.23 or 3.42; 3.73 with Max Trailering Package

Chassis / Suspension

Front:	independent coil-over-shock; twin-tube shock absorbers; monotube shocks with Z71
Rear:	solid axle with semi-elliptic, variable-rate, two-stage multileaf springs; splayed shock absorbers; twin-tube shock absorbers; monotube shocks with Z71
Steering type:	electric power-assisted rack-and-pinion
Steering ratio:	16.3:1
Steering wheel turns, lock-to-lock:	3.03
Turning circle, curb-to-curb (ft / m):	2WD with 5' 8" box: 47.2 / 14.4 4WD with 5' 8" box: 47.2 / 14.4 2WD with 6' 6" box: 48.5 / 14.8 4WD with 6' 6" box: 48.5 / 14.8

Brakes

Type:	power-assisted, four-wheel disc, four-wheel ABS, with Duralife™ rotors; vented front rotors
Rotor diameter x thickness (in / mm)	front: 13 x 1.18 / x 330 x 30 rear: 13.6 x 0.79 / 345 x 20
Total swept area (sq in / sq cm)	front: 250 / 1612 rear: 252 / 1628

Wheels / Tires

Wheel size & type:	17 x 8-in. steel (std. 1WT) 17 x 8-in. stainless steel-clad (std. 2WT) 17 x 8-in. bright machined aluminum (std. LT, Z71 w/LT) 18 x 8.5-in. bright machined aluminum (std. LTZ, Z71 w/LTZ; avail. LT, Z71 w/LT) 20 x 9-in. polished aluminum (avail. LT, Z71 w/LT) 20 x 9-in. chrome aluminum (std. High Country; avail. LTZ, Z71 w/LTZ)
Tires:	P245/70R17 all-season, blackwall P265/70R17 all-season, blackwall P265/70R17 all-terrain, blackwall LT265/70R17 all-terrain, blackwall P265/65R18 all-season, blackwall P265/65R18 all-terrain, blackwall or white-outlined letter P275/55R20 all-terrain, blackwall P275/55R20 all-season, blackwall

Dimensions

Exterior

	Crew Cab with 5' 8" box	Crew Cab with 6' 6" box
Wheelbase (in / mm):	143.5 / 3645	153 / 3886
Overall length (in / mm):	230 / 5843	239.6 / 6085
Overall width (in / mm):	80 / 2032	80 / 2032
Overall height (in / mm)		
2WD:	74.2 / 1884	73.7 / 1873
4WD:	74.0 / 1879	73.8 / 1875
Track (in / mm)		
2WD front:	68.8 / 1747	68.8 / 1747
2WD rear:	67.6 / 1716	67.6 / 1716
4WD front:	68.7 / 1745	68.7 / 1745
4WD rear:	67.6 / 1716	67.6 / 1716
Min. running ground clearance (in / mm):		
2WD:	8.7 / 222	8.5 / 216
4WD:	8.9 / 226	8.9 / 227
Ground to top of load floor (in / mm):		
2WD:	34.9 / 886	34.4 / 874
4WD:	34.3 / 872	34.1 / 867
Step-in height		
2WD:	22.3 / 566	21.9 / 557
4WD:	22.2 / 564	22.1 / 562
Approach angle (deg)		
2WD:	17.7	17.2
4WD:	17.9	18.0
Breakover angle (deg)		
2WD:	19.2	17.5
4WD:	19.0	17.7
Departure angle (deg)		
2WD:	23.9	23.3
4WD:	23.3	23.0

Cargo box

	Crew Cab with 5' 8" box	Crew Cab with 6' 6" box
Cargo volume (cu ft / L):	53.4 / 1512	61 / 1728
Length at floor (in / mm):	69.3 / 1761	78.9 / 2003
Width at floor (in / mm):	64.6 / 1642	64.6 / 1642
Width between wheelhousings (in / mm):	51 / 1296	51 / 1296
Tailgate width (in / mm):	62.2 / 1579	62.2 / 1579
Inside height (in / mm):	21.1 / 536	21.1 / 536

Interior

	Crew Cab, Front	Crew Cab, Rear
Headroom (in / mm):	42.8 / 1087	40.5 / 1029
Legroom (in / mm):	45.3 / 1150	40.9 / 1040
Shoulder room (in / mm):	64.8 / 1647	65.7 / 1670
Hip room (in / mm):	60.7 / 1543	60.3 / 1531

Curb weight & payload

	GVWR (lb / kg)	Minimum Curb Weight (lb / kg)	Max. Payload (lb / kg)	Weight Distribution (% front / rear)
2WD:				
Crew Cab, 5' 8"	6900 / 3130 (4.3L)	4942 / 2241 (4.3L)	1933 / 877 (4.3L)	56 / 44

box	7000 / 3175 (5.3L)	5042 / 2287 (5.3L)	1933 / 877 (5.3L)	
Crew Cab, 5' 8" box with Max Trailering Package	7200 / 3266 (5.3L)	5168 / 2344 (5.3L)	2007 / 910 (5.3L)	56 / 44
Crew Cab, 6' 6" box	6900 / 3130 (4.3L) 7000 / 3175 (5.3L)	5000 / 2268 (4.3L) 5104 / 2315 (5.3L)	1875 / 850 (4.3L) 1871 / 848 (5.3L)	57 / 43
Crew Cab, 6'6" box with Max Trailering Package	7200 / 3266 (5.3L)	5229 / 2372 (5.3L)	1947 / 883 (5.3L)	57 / 43
4WD:				
Crew Cab, 5' 8" box	7100 / 3220 (4.3L) 7200 / 3266 (5.3L)	5139 / 2331 (4.3L) 5218 / 2367 (5.3L)	1936 / 878 (4.3L) 1957 / 887 (5.3L)	58 / 42
Crew Cab, 5' 8" box with Max Trailering Package	7200 / 3266 (5.3L)	5345 / 2424 (5.3L)	1830 / 830 (5.3L)	58 / 42
Crew Cab, 6' 6" box	7100 / 3220 (4.3L) 7200 / 3266 (5.3L)	5197 / 2357 (4.3L) 5292 / 2400 (5.3L)	1878 / 852 (4.3L) 1883 / 854 (5.3L)	59 / 41
Crew Cab, 6'6" box with Max Trailering Package	7200 / 3266 (5.3L)	5424 / 2460 (5.3L)	1751 / 794 (5.3L)	59 / 41

Capacities

	Crew Cab, 5' 8" box	Crew Cab, 6' 6" box	
Seating:	5 or 6	5 or 6	
Fuel tank (gal / L):	26 / 98	26 / 98	
	EcoTec3 4.3L	EcoTec3 5.3L	EcoTec3 6.2L
Engine oil (qt / L):	6 / 5.6 (Dexos 5W30)	8 / 7.5 (Dexos 0W20)	8 / 7.5 (Dexos 0W20)
Cooling system (qt / L):	14.8 / 14	15.6 / 14.8	15.6 / 14.8

Trailering – maximum with ball hitch

2WD:	
Crew Cab, 5' 8" box	5900 / 2676 – 4.3L (3.23 axle) 9800 / 4445 – 5.3L (3.42 axle)
Crew Cab, 5' 8" box w/ Max Trailering Package	11400 / 5171 – 5.3L (3.73 axle)
Crew Cab, 6' 6" box	5800 / 2630 – 4.3L (3.23 axle) 9700 / 4400 – 5.3L (3.42 axle)
Crew Cab, 6' 6" box w/ Max Trailering Package	11300 / 5125 – 5.3L (3.73 axle)
4WD:	
Crew Cab, 5' 8" box	6700 / 3039 – 4.3L (3.42 axle) 9600 / 4354 – 5.3L (3.42 axle)
Crew Cab, 5' 8" box w/ Max Trailering Package	11200 / 5080 – 5.3L (3.73 axle)
Crew Cab, 6' 6" box	6600 / 2994 – 4.3L (3.42 axle) 9500 / 4309 – 5.3L (3.42 axle)
Crew Cab, 6' 6" box w/ Max Trailering Package	11100 / 5035 – 5.3L (3.73 axle)

Note: Information shown is current at time of publication. Visit <http://media.gm.com> for updates.