



CUSHMAN

MODEL: HAULER 1200
TYPE: GASOLINE POWERED TRUCK
MODEL YEAR: 2012
Part No.: 618843



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 13 hp (9.7 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Ignition:** Electronic spark/magneto
- **Air Cleaner:** Replaceable dry cartridge

Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

Drive Train: Automatic, continuously variable transmission (CVT)

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system

Transaxle: Differential with helical gears, ground speed governor, forward/reverse

Cargo Bed: Roto-molded cross-linked polyethelene. Lifts for access to powertrain. Removable hinged multi-position tailgate requires no latch mechanism

PRODUCT OVERVIEW

Dimensions

Overall Length	113 in (287 cm)
Overall Width	49.5 in (128 cm)
Overall Height (No Canopy)	46.5 in (118 cm) (Top of steering wheel)
Overall Height (With Canopy)	70.0 in (178 cm)
Wheel Base	77.0 in (196 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.0 in (97 cm)
Gnd Clearance @ Differential	4.3 in (11 cm)
Cargo Box Width (inside)	44.0 in (112 cm)
Cargo Box Length (inside)	36.0 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)
Cargo Box Capacity	9.6 cu ft (0.27 m3)
Cargo Box material	Roto-molded polyethylene

Vehicle Power

Power Source	4 Cycle 24.5 cu in (401 cc)
Valve Train	Single Cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Batteries (Qty, Type)	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal
Air Cleaner	Replaceable Dry Cartridge
Lubrication	Pressurized Oil System
Oil Filter	Spin-On
Cooling System	Air Cooled
Fuel Capacity	5.8 Gallon (22.0 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward - Reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

Performance

Seating Capacity	2 Persons
Dry Weight	938 lb (425 kg)
Curb Weight	978 lb (443 kg)
Bed Load Capacity	800 lb (365 kg)
Vehicle Load Capacity	1200 lb (545 kg)
Outside Clearance Circle	22.0 ft (6.7 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	Fwd - 16.5 mph ± 0.5 mph (25.7 kph ± 0.8 kph) Rev - 11.6 mph ± 0.5 mph (18.6 kph ± 0.8 kph)
Towing Capacity	720 lb (360 kg) max load

Steering & Suspension

Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	Links 18 x 8.50 - 8 (4 Ply Rated)
Rear Tires	Turf Saver 20 x 10.0 - 8

Body & Chassis

Frame	Welded steel with DuraShield™ powder coat
Front Body & Finish	Injection Molded TPO
Rear Body & Finish	Steel. Base coat/clear coat
Standard Color	Hunter Green

Some items shown may be optional equipment



CUSHMAN

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld	Item	Std	Opt	Fld
TIRES & WHEELS:				ELECTRICAL:			
Front:				Battery Chargers:			
Links 18 x 8.50 - 8 (4 Ply Rated)	●			48 VDC Delta Q, 120/230 VAC 50/60 Hz w/18' DC Cord	●		
USA Trail 18 x 8.50 - 8 (Load Range C)		●		48 VDC - SCR		●	
Turf Saver 18 x 8.50 - 8 (Load Range B)		●		48 VDC - 230 VAC 60 Hz		●	
Rear:				48 VDC - 120 VAC 60 Hz		●	
Links 18 x 8.50 - 8 (4 Ply Rated)	●			Battery Charger Delete		●	
USA Trail 18 x 8.50 - 8 (Load Range C)		●		Other:			
Turf Saver 18 x 8.50 - 8 (Load Range B)		●		Unique Individual Key Switch		●	
Wheel Covers:				Headlights	●		
Spoke, Black & Gold		●		Headlights & Taillights		●	
Spoke, Black & Silver		●		Brake Lights		●	
COLORS:				Turn Signals with 4-Way Flashers		●	
Body Color - Hunter Green	●			Strobe Light		●	
Body Color - Ivory		●		Work Lights		●	
Body Color - Bright White		●		Work Lights with Strobe Light		●	
Body Color - Yellow		●		Miscellaneous:			
Body Color - Orange		●		DC Converter		●	
Custom Body Color		●		Non Standard Battery Option		●	
Seat Color - Tan		●		Hour Meter		●	
Seat Color - Oyster		●		WEATHER PROTECTION:			
Seat Color - Gray	●			Sun Canopy (Top) Black			●
Seat Color - White		●		Windshield Fold Down			●
HAULING & TOWING:				Weather Enclosure (3 Side, Top & Windshield Req'd)			●
2 in (5 cm) Receiver (Rear)		●		Windshield Flat			●
1 7/8 in (48 mm) Ball (Rcvr Reqd)		●		Windshield Fold Down			●
Angle (Rcvr Reqd)		●		TRANSAXLE:			
Clevis (Rcvr Reqd)		●		Limited Slip Differential		●	
Angle, Drop (Rcvr Reqd)		●		VEHICLE CAB:			
1 7/8 in (48 mm) Ball, Drop (Rcvr Reqd)		●		Steel Cab (Tan):			●
Clevis, Drop (Rcvr Reqd)		●		Steel Cab (White):			●
Power Dump (Electric)		●		Steel Cab (Custom Color):			●
Trailer, Dump (Steel Bed)			●	Beacon, Amber (Cab Required)			●
Trailer, Dump (Poly Bed)			●	Defroster/Fan (Cab Required)			●
Aluminum Bed		●		Dome Light (Cab Required)			●
OTHER PERFORMANCE:				Doors (Steel) Tan (Cab Required)			●
Ash Tray		●		Doors (Steel) White (Cab Required)			●
Differential Guard		●		Doors (Steel) Custom Color (Cab Required)			●
Front Hydraulic Disc Brakes		●		Doors (Vinyl) Tan (Cab Required)			●
Front Fascia & Brush Guard (Black)		●		Rear View Mirror (Cab Required)			●
Glove Box Door (Locking) Driver Side		●		Strobe Light (Cab Required)			●
Glove Box Door (Locking) Passenger Side		●		Windshield Wiper (Cab Required)			●
Horn	●			Work Light (Cab Required)			●
State of Charge Meter	●						
International Tire		●					
International Brushguard		●					
International Fender Flare		●					
Canopy Handle			●				