

Building a better world around you

- Small in size Big in lifting power Versatile hydraulic quick change attachments Easy to operate Reliable / Durable Service and maintenance ease Operator friendly environment Low operating cost Customer support





Sales • Service • Parts Distributed by:

When Your Business Depends On The Right Choice, The Right Choice is "Coyote!"

COYOTE C170B

Hydrostatic Drive Wheel Loader: Powerful •

Engine

Make: Perkins diesel Type: 403D-11 Output: 24.8 hp # of cylinders: 3 Dry-type air cleaner with electric display.

■ Undercarriage

Rear axle oscillation, $\pm 12.5^{\circ}$ Axles with planetary reduction gears in wheel hubs. Self locking differentials

Electrical System

Operating Voltage: 12 V Battery: 1 x 12 V, 100 Ah Alternator: 600 W Starter: 12 V

■ Operating Data (Bucket)

Standard Bucket Capacity: .50 cu yd Bucket Width: 4 ft 9 in Width Over Tires: 3 ft 4 in. Breakout Force: 1102 lbs. Service Weight: 3,240 lbs.

■ Transmission

Hydrostatic drive with automotive-type variable speed control. Automatic torque output variation to meet operating demands. Work speed range: 0 - 4 mph. Travel speed range: 0 - 7 mph.

Tires

Low pressure tires 27x8.5-15 Wide tires 26x12-12

Loading Equipment

Kinematics for high breakout force, fast dumping, parallel action, automatic bucket return to dig position.

Single lever for easy control. Float position. 3rd control circuit.

Silent

Brakes

Disc brakes on the rear axle.

Steering

Center point frame articulation Front and rear wheels follow the same track. Load sensing hydraulic system. Steering angle 34° to either side.

Economical

Hydraulic System


Gear type pump for loading and steering hydraulics, two lifting cylinders and one tilting cylinder. Operating pressure: 2,320 psi.

Standard Equipment

Rapid changeover system, hydraulic. Rear-view mirrors on both sides. Deluxe driver's seat with safety belt. 3rd control circuit Reversing lights

Optional Equipment

Pallet fork General purpose buckets Additional attachments available.



А	7'5"
В	2'6"
С	4'6"
D	4'10"
Е	12'1"
F	8"
G	2"
Н	6'6"
Ι	7'5"
J	1'9"

* Information herein is not warranted and subject to change without notice. Coyote Loaders or its agents will not assume any liability for errors.